

Quotation Request //

US Government Printing Office

Agency Publishing Services
732 North Capitol Street, NW
Washington DC 20401-0001

JACKET:344-697 R-5

Quotations are Due By:

(Eastern Time)10:00 AM on 10/20/2008

Submit Fax Quotes to:00000000

Contractors must provide mandatory taxpayer information before GPO makes payment.

Please see special notice on <http://contractorconnect.gpo.gov/>.

TITLE: Certificate Holders

QUANTITY: 400 Padded Vinyl Certificate Holders Total. 100 on maroon vinyl (Distinguished Service Award) with gold stamping and 300 on blue vinyl (Meritorious Service Award) with silver stamping.

TRIM SIZE: Approx. 23 x 14-1/2" flat; Folded size of 11-1/2 x 14-1/2"

PAGES: Printing on outside front cover only

SCHEDULE:

Furnished Material will be available for pickup by 10/20/2008

Deliver complete (to arrive at destination) by 12/15/2008

F.O.B. destination

QUALITY LEVEL: 3 Quality Assurance Through Attributes (GPO PUB 310.1, effective May 1979 (Rev. 8-02)) applies.

DESCRIPTION:

Outside front cover stamps a 3" diameter fine line seal and 2 bold type lines. Approx stamping area is 5-3/4 x 4-3/4". Imitation silver foil equal to Transfer Print 113 silver foil and the imitation gold foil equal to Transfer Print 404 gold foil. Stamping must have solid impressions - no picking, pinholes or filled letters.

Construction: Folders to be constructed of 2 binders board (approx. 11-1/4 x 14-1/2") exact size to be determined by contractor, including an approx 1/2" backbone so the flat size is 23 x 14-1/2". The boards are to be completely covered on the outer surface with foam padding securely glued and both boards encased in an outer cover of vinyl which is to be glued at all edges. Reinforce gutter with a strip of vinyl at least 2" wide on the inside. The inside layer of vinyl for the front and back covers each must have four triangular shaped corner pieces approx. 1-3/4" on the right angle sides positioned to hold an 11 x 14" document and protective cover. All edges are to have at least 1/2" turn in on all sides.

Note: The surface of the cover stock may require that the outer edge (turn-in) be treated to insure complete bonding of the adhesive.

MATERIAL FURNISHED: Contractor to pickup at GPO. One CD with disk info sheets, a sample, and a set of laser copies. Contractor to make stamping dies.

Electronic media generated on a Macintosh using InDesign CS3 and Photoshop CS2. Files are in native format or print-to-file postscript format. All printer and screen fonts are included. Color system used is CMYK or Pantone. Files provide for bleeds and graphics are properly linked.

Prior to image processing, the contractor is responsible for performing a basic check (preflight) of the furnished publishing files to assure accurate output of the required reproduction image. Any errors, media damage or data corruption that might interfere with proper file imaging must be reported to the contract administrator in sufficient time to comply with the shipping schedule. In addition, the contractor is responsible for creating or altering any necessary trapping, setting proper screen angles and screen

frequency, and defining file output selection for the imaging device being utilized. All furnished files must be imaged as necessary to meet assigned quality level.

PAPER: * Must be in accordance with JCP Paper Specification Standards in effect on date of this order

Cover material - Maroon and Blue vinyl equal to Holliston Acro-flex 7, Maroon Steer & Blue Steer.

Binder boards - No. 1 quality, 0.125 thick.

Lining cloth - White moire rayon, silk or nylon with a moisture resistant finish.

Corner Cloth-

Maroon Binders: Maroon moire rayon, silk or nylon with a moisture resistant finish.

Blue Binders: Dark blue moire rayon, silk or nylon with a moisture resistant finish.

Protective cover - Crystal Clear vinyl or acetate, approx. 0.010" thick.

Padding - Flame retardant foam polyurethane polymer, density: 1.7 to 1.9 pounds per cubic foot, thickness 0.125" +/- 0.015".

Suitable tissue insert approx. 11 x 14" for both inside covers.

COLOR OF INK:

PMS 877 Silver & PMS 872 Gold

MARGINS: Follow Copy Sample. Adequate Gripper.

PROOFS:

PRIOR TO PRODUCTION SAMPLES - 3 day hold: The sample requirement for this contract is not less than five (5) printed copies. Each sample must be constructed as specified using the form, ink, equipment, and methods of production which will be used in producing the finished product. Paper used for samples must be of the size, kind, and quality the contractor will furnish.

Samples will be inspected and tested and must comply with the specifications as to kind and quality of materials, quality of reproduction, and satisfactory processing on the machine indicated. Prior to the commencement of production of the contract production quantity, the contractor shall submit samples to the AGENCY in distribution section.

Samples will be tested for conformance of materials and/or will be tested for usage on the specified equipment and/or for construction. The container and accompanying documentation shall be marked PREPRODUCTION SAMPLES and shall include the GPO jacket and purchase order. The samples must be submitted in sufficient time to allow Government testing of the samples and production and shipment in accordance with the shipping schedule.

The Government will approve, conditionally approve, or disapprove the samples within 3 workdays of the receipt thereof. Approval or conditional approval shall not relieve the contractor from complying with the specifications and all other terms and conditions of the contract. A conditional approval shall state any further action required by the contractor. A notice of disapproval shall state the reasons therefore.

If the samples are disapproved by the Government, the Government, at its option, may require the contractor to submit additional samples for inspection and test, in the time and under the terms and conditions specified in the notice of rejection. Such additional samples shall be furnished, and necessary changes made, at no additional cost to the Government and with no extension in the shipping schedule. The Government will require the time specified above to inspect and test any additional samples required.

In the event the additional samples are disapproved by the Government, the contractor shall be deemed to have failed to make delivery within the meaning of the default clause in which event this contract shall be

subject to termination for default, provided however, that the failure of the Government to terminate the contract for default in such event shall not relieve the contractor of the responsibility to deliver the contract quantities in accordance with the shipping schedule.

In the event the Government fails to approve, conditionally approve, or disapprove the samples within the time specified, the Contracting Officer shall automatically extend the shipping schedule in accordance with Contract Clause 12, "Notice of Compliance With Schedules," of GPO Contract Terms (GPO Publication 310.2, effective December 1, 1987 (Rev. 6-01)).

Manufacture of the final product prior to approval of the sample submitted is at the contractor's risk. Samples will not be returned to the contractor. All costs, including the costs of all samples shall be included in the contract price for the production quantity.

All samples shall be manufactured at the facilities in which the contract production quantities are to be manufactured.

Send prior-to production samples, together with the furnished media (lasers and electronic files) by traceable means: U.S. Nuclear Regulatory Commission, 11555 Rockville Pike, Rockville, MD 20852. Attn: Dist SUVs, O-P1-37, Barbara H. Blount, (301) 415-0535.

PACKING:

Pack each item separate and identify.

Pack 100 per shipping container.

DISTRIBUTION:

400 Certificate Holders and all GFM and BOTH STAMPING DIES to: USNRC, 11555 Rockville Pike, Rockville, MD 20852. Attn: Dist Srvs, O-P1-37, Barbara H. Blount 301-415-0535.

QUALITY ASSURANCE LEVELS AND STANDARDS: The following levels and standards shall apply to these specifications:

Inspection Levels (from ANSI/ASQC Z1.4):

(a) Non-destructive Tests -- General Inspection Level I.

(b) Destructive Tests -- Special Inspection Level S-2.

Specified Standards-- The specified standards for the attributes requiring them shall be:

ATTRIBUTE

SPECIFIED STANDARD

P-7. Type Quality and Uniformity

Camera Copy